





## INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

<b>(51) International Patent Classification <sup>7</sup> :</b>  <b>H04Q 7/38</b>	<b>A1</b>	<b>(11) International Publication Number:</b> <b>WO 00/11903</b>  <b>(43) International Publication Date:</b> 2 March 2000 (02.03.00)
<b>(21) International Application Number:</b> PCT/SE99/01351  <b>(22) International Filing Date:</b> 6 August 1999 (06.08.99)  <b>(30) Priority Data:</b> 60/097,686                      24 August 1998 (24.08.98)                      US 09/348,048                      7 July 1999 (07.07.99)                      US  <b>(71) Applicant:</b> TELEFONAKTIEBOLAGET LM ERICSSON (publ) [SE/SE]; S-126 25 Stockholm (SE).  <b>(72) Inventors:</b> MALMGREN, Göran; Gösta Ekmansväg 5, 5 tr, S-129 35 Hägersten (SE). LARSSON, Mikael; Lilla slingan 18, S-192 73 Sollentuna (SE). LARSSON, Peter; 4b Park Vale, #01-01 Euro Asia View, Singapore 288564 (SG). LI, Hui; Berliner Platz 12, D-90489 Nürnberg (DE).  <b>(74) Agent:</b> ERICSSON RADIO SYSTEMS AB; Patent Sup- port/Ericsson Research, S-164 80 Stockholm (SE).		<b>(81) Designated States:</b> AE, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CR, CU, CZ, DE, DK, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, UA, UG, UZ, VN, YU, ZA, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SL, SZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).  <b>Published</b>  <i>With international search report.</i> <i>Before the expiration of the time limit for amending the</i> <i>claims and to be republished in the event of the receipt of</i> <i>amendments.</i>
<b>(54) Title:</b> MOBILE TERMINAL INITIATED AND ASSISTED ANTENNA SELECTION		
<pre> sequenceDiagram     participant BS     participant NT     BS-&gt;&gt;NT: TRANSMISSION OF SECTOR MESSAGES (205)     activate NT     NT-&gt;&gt;NT: SELECTION OF A SECTOR (210)     NT-&gt;&gt;BS: SUGGESTION FOR AN ANTENNA (215)     deactivate NT     BS-&gt;&gt;NT: CONFIRMATION OF THE SUGGESTION (220)     deactivate BS       </pre>		
<b>(57) Abstract</b>  In a cellular, broadband radio access network, such as a High Performance Local Area Network Type 2 (HIPERLAN/2), which employs multiple antennas per base station, the process of identifying and selecting the most appropriate base station antenna to support a given mobile terminal may be accomplished more effectively by allowing the mobile terminal to initiate antenna selection and, thereafter, to identify the most appropriate one of the multiple base station antennas. By utilizing the mobile terminal in this capacity, the process of antenna selection can be accomplished more effectively even if there is relatively little uplink communication between the mobile terminal and its corresponding base station.		

**FOR THE PURPOSES OF INFORMATION ONLY**

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece	ML	Mali	TR	Turkey
BG	Bulgaria	HU	Hungary	MN	Mongolia	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MR	Mauritania	UA	Ukraine
BR	Brazil	IL	Israel	MW	Malawi	UG	Uganda
BY	Belarus	IS	Iceland	MX	Mexico	US	United States of America
CA	Canada	IT	Italy	NE	Niger	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NL	Netherlands	VN	Viet Nam
CG	Congo	KE	Kenya	NO	Norway	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NZ	New Zealand	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	PL	Poland		
CM	Cameroon	KR	Republic of Korea	PT	Portugal		
CN	China	KZ	Kazakstan	RO	Romania		
CU	Cuba	LC	Saint Lucia	RU	Russian Federation		
CZ	Czech Republic	LI	Liechtenstein	SD	Sudan		
DE	Germany	LK	Sri Lanka	SE	Sweden		
DK	Denmark	LR	Liberia	SG	Singapore		
EE	Estonia						

## MOBILE TERMINAL INITIATED AND ASSISTED ANTENNA SELECTION

5

### FIELD OF INVENTION

10           The present invention relates to mobile communications systems. More particularly, the present invention relates to the selection of one or more adaptive or sector antennas in a mobile communications system that employs multiple antennas per base station.

15

### BACKGROUND

          HIPERLAN/2 is a short-range, high data rate, cellular, broadband radio access network, which is mainly intended for indoor operations such as offices, conference halls, exhibitions, airports and home environments. Some outdoor scenarios are also being considered (e.g., campus areas and concentrated urban areas). The frequency spectrum to be used for H/2 is currently unlicensed. Thus, several "operators" may use the same frequency spectrum simultaneously. Furthermore, the available frequency spectrum for this system is very limited; consequently, it has been questioned whether it is possible to deploy such a cellular network.

25

          Adaptive and/or sector antennas can be utilized to improve the capacity in such networks. With these antennas, a base station (BS) can restrict its transmission to a more definitive area or sector in which a given mobile terminal (MT) is located. Thus, radiated power into nearby areas or sectors, and interference to surrounding cells can be drastically reduced, as illustrated in

30   FIG. 1.

-2-

Generally, in systems that employ these techniques, the uplink signaling is transmitted before the downlink signaling. The BS can then use the uplink signal to measure the relative direction of the MT. Upon determining the direction of the MT, the BS selects one of several antennas for communicating with the MT.

5 However, this general procedure is often unacceptable, particularly when only downlink traffic is present, as the BS has no uplink signal with which to measure the relative direction of the MT. Accordingly, it would be more advantageous if the MT initiated and selected the BS antenna, rather than the BS, since the MT always knows its location. Presently, though, there exists no such protocol or

10 technique.

### SUMMARY OF THE INVENTION

The present invention involves a technique that improves the capacity in cellular, broadband radio access networks that employ multiple antenna base stations (BSs), where each cell is divided into sectors and each base station

15 antenna is associated with a corresponding sector. Unlike conventional techniques, mobile terminals (MTs) in the present invention are employed to identify the most appropriate BS antenna from amongst multiple BS antennas. By using the MTs to identify the most appropriate BS antenna, rather than the BS, the

20 BS antenna selection process is accomplished more efficiently and effectively, even when there is no significant uplink transmission between a given MT and the BS.

Accordingly, it is an objective of the present invention to improve the BS antenna selection process in a cellular, broadband radio access network that

25 employs multiple antennas per BS.

It is also an objective of the present invention to improve the signal quality of the communication links between the MTs and the corresponding BS which employs multiple antennas.

It is still another objective of the present invention to reduce or minimize

-3-

radiated energy and interference levels in other sectors or other cells proximally located to the sector in which a given MT is presently operating.

In accordance with one aspect of the present invention, the above-identified and other objectives are achieved through a method and a corresponding apparatus for selecting one of several base station antennas, wherein each of the base station antennas covers a corresponding sector of a cell associated with the base station. The method and corresponding apparatus involve transmitting a number of sector messages from the base station, where each sector message is associated with a corresponding sector of the cell. At a mobile terminal, the sector messages transmitted by the base station are received. The mobile terminal then determines a signal quality associated with each of the received sector messages, and based on this determination, the mobile terminal selects one of the antennas. The mobile terminal then transmits an antenna selection request message to the base station.

15

### BRIEF DESCRIPTION OF THE FIGURES

The objectives and advantages of the present invention will be understood by reading the following detailed description in conjunction with the drawings, in which:

- FIG. 1 illustrates a multi-sectored cell;
- FIG. 2 depicts a technique for selecting a sector in accordance with an exemplary embodiment of the present invention;
- FIG. 3 depicts a MAC frame in accordance with an exemplary embodiment of the present invention; and
- FIG. 4 depicts the format of a downlink channel of a MAC frame in accordance with an exemplary embodiment of the present invention.

25

### DETAILED DESCRIPTION OF THE INVENTION

The present invention involves the selection of one or more antennas in a mobile communications system, and more specifically, a broadband radio access

-4-

network within a mobile communications system that employs multiple antennas per base station (BS), wherein the cells are divided into a plurality of sectors, and wherein each sector is supported by a corresponding antenna transceiver. In general, a mobile terminal (MT), in accordance with exemplary embodiments of the present invention, measures the signal quality associated with each of a number of downlink signals, where each downlink signal is associated with a different, corresponding sector in the cell in which the MT is currently operating. Then, based on the signal quality measurements, the MT informs the corresponding BS which of the several antennas is preferable.

FIG. 2 illustrates a signaling strategy 200 between a BS and a MT, in accordance with exemplary embodiments of the present invention. It will be understood that the arrows directed from the BS to the MT represent downlink channel transmissions and the arrow directed from the MT to the BS represents an uplink channel transmission.

In a first step 205, the BS transmits a sector message for each sector in a corresponding portion of the downlink channel. Each sector message includes, among other things, an antenna identity associated with the corresponding antenna and a starting location of and a total amount of the random access channel, within a present data frame, allocated to the corresponding sector.

The second step 210 in the signaling strategy 200 involves the selection of an antenna by the MT. The MT, upon receiving one or more of the sector messages, determines a value associated with any of a number of signal quality measurements for each of the one or more sector messages received. Then, based on these signal quality measurements, the MT selects a particular antenna that is most likely to guarantee satisfactory reception quality. For example, the MT might take into consideration such signal quality measurements as bit error rate (i.e., BER), signal strength, C/I ratio and/or delay spread. However, it will be understood that in deciding whether to select one antenna over another, the MT may take into consideration factors other than those directly related to signal

-5-

reception quality. Therefore, the MT might ultimately select an antenna that does not guarantee the best signal reception quality. It will also be understood that the MT might receive each of the one or more sector messages from the BS over a single data frame or over several data frames.

5           Based on the result of step 210 described above, the MT may transmit a connection set-up request or a change of antenna request to the BS, as illustrated in step 215. The MT may, of course, transmit such a request in that portion of the uplink channel (e.g., the random access channel) reserved for the sector corresponding to the selected antenna, or in the particular case of a change of  
10 antenna request, in that portion of the uplink channel allocated to the sector corresponding to the antenna through which the MT is presently communicating.

          The fourth step 220 involves the transmission of a confirmation message from the BS to the MT over the downlink channel. After receiving the connection set-up request or the change of antenna request from the MT, the BS determines  
15 whether to approve the MT's request. If the BS does approve the request, the BS transmits confirmation of such to the MT. However, there are a number of circumstances under which a BS might not approve a MT's antenna selection request. For example, a BS might disapprove a request based on an excessive amount of traffic in the sector associated with the selected antenna. In another  
20 example, the sector associated with the selected antenna may be void of any other MTs, wherein the BS may determine that the amount of overhead processing required to support a single MT in that sector is excessive and not worth the additional signal reception quality that the MT might achieve by transmitting and receiving through the selected antenna.

25           In HIPERLAN/2 systems, the signaling strategy of the present invention may be integrated into the design of a MAC protocol, as illustrated in FIGs. 3 and 4. For HIPERLAN/2 systems with sectorized antennas, the MAC frame header may consist of several sector headers 1...N, each being transmitted separately in a broadcast message by the corresponding sectorized antenna. The content of each



-6-

sector header would depend on the corresponding sector, and it would include, for example, the identity of the corresponding antenna, the identity of that portion of the downlink channel allocated to the sector, and the identity of that portion of the random access channel allocated to the sector.

5       The downlink and uplink channel transmissions associated with each sector are multiplexed into the downlink and uplink channel of the MAC frame, respectively. For example, at the beginning of the downlink channel associated with a sector  $m$ , as illustrated in FIG. 4, several broadcast control protocol data units (C-PDUs) are transmitted. A broadcast C-PDU can be utilized to inform a  
10       given MT as to whether the BS has approved or disapproved the MT's connection set-up request or change of antenna request.

For systems employing multiple antennas per BS, the random access channel of a MAC protocol frame, like the MAC header, may also be divided into several parts, wherein each part is associated with one of a number of sectors  
15       1...N corresponding to each of a number of antennas. The length of each part being determined based on the traffic load in the sector 1...N corresponding to each antenna. As stated above, a MT may transmit an antenna selection request in that portion of the random access channel allocated to the sector 1...N  
corresponding to the selected antenna, or, alternatively, in that portion of the  
20       random access channel allocated to the sector 1...N corresponding to the antenna through which the MT is currently transmitting.

The present invention has been described with reference to a number aspects and various exemplary embodiments. However, it will be readily apparent to those skilled in the art that it is possible to embody the invention in specific  
25       forms other than those described above without departing from the spirit of the invention. The various aspects and exemplary embodiments are illustrative, and they should not be considered restrictive in any way. The scope of the invention is given by the appended claims, rather than the preceding description, and all variations and equivalents thereof which fall within the range of the claims are

-7-

intended to be embraced therein.

**WHAT IS CLAIMED IS:**

1. In a mobile communications system that employs a base station having  
5 multiple base station antennas, wherein each of the multiple base station antennas covers a corresponding sector of a cell associated with the base station, a method for selecting one of the multiple base station antennas comprising the steps of:  
transmitting a plurality of sector messages from the base station, wherein  
each the plurality of sector messages is associated with a corresponding sector of  
10 the cell;  
receiving the plurality of sector messages transmitted by the base station at  
a mobile terminal and determining a signal quality associated with each of the  
plurality of received sector messages;  
at the mobile terminal, selecting one of the multiple antennas as a function  
15 of the signal quality determination; and  
transmitting an antenna selection request message from the mobile terminal  
to the base station.
2. The method of claim 1 further comprising the steps of:  
20 receiving the antenna selection request message from the mobile terminal at  
the base station;  
at the base station, determining whether the antenna selection request  
message is to be approved; and  
transmitting an antenna selection request approval confirmation to the  
25 mobile terminal if the base station determines that the sector selection request is  
approved.
3. The method of claim 2 wherein said step of determining whether the  
antenna selection request message is to be approved comprises the step of:

-8-

determining a traffic load associated with the sector corresponding to the selected antenna.

4. The method of claim 1 wherein the plurality of sector messages are transmitted from the base station in a single transmission frame.
5. The method of claim 1 wherein the plurality of sector messages are separately transmitted in more than one transmission frame.
6. The method of claim 1 wherein said step of determining the signal quality associated with each of the plurality of received sector messages comprises the steps of:
  - measuring any of bit error rate, signal strength, carrier to interference ratio and delay spread associated with each of the plurality of sector messages.
7. The method of claim 1 wherein said step of transmitting an antenna selection request message from the mobile terminal to the base station comprises the step of:
  - inserting the antenna selection request message into a portion of a random access channel of a mobile access protocol specifically reserved for the selected antenna.
8. The method of claim 1 wherein the antenna selection request is part of a connection set-up request generated by the mobile terminal.
9. The method of claim 1 wherein the antenna selection request is part of a change of antenna request generated by the mobile terminal.
10. The method of claim 9 wherein said step of transmitting an antenna

-9-

selection request message from the mobile terminal to the base station comprises the step of:

inserting the antenna selection request message into a portion of an uplink channel of a mobile access protocol specifically reserved for an antenna through  
5 which the mobile terminal is presently operating.

11. In a mobile communications system that employs multiple antennas in a base station, wherein each of the multiple antennas provides coverage for a corresponding sector area associated with the base station, an apparatus for  
10 selecting one of the multiple antennas comprising:

transmission means for sending one or more sector messages from a base station,

reception means for receiving the one or more sector messages transmitted by the base station at a mobile terminal and processing means for determining the  
15 signal reception quality associated with each of the one or more received sector messages;

at the mobile terminal, selection means for identifying one of the multiple antennas as a function of the signal reception quality determination; and

transmission means for sending an antenna selection request message from  
20 the mobile terminal to the base station.

12. The apparatus of claim 11 further comprising:

reception means for receiving the antenna selection request message from the mobile terminal at the base station;

25 at the base station, processing means for determining whether the antenna selection request in the antenna selection request message is to be approved; and

transmission means for sending an antenna selection request approval confirmation to the mobile terminal if the base station determines that the antenna selection request is approved.

-10-

13. The apparatus of claim 12 wherein said processing means for determining whether the antenna selection request is to be approved comprises:

processing means for determining a traffic load associated with the sector area corresponding to the selected antenna.

5

14. The apparatus of claim 11 wherein the one or more sector messages are transmitted from the base station in a single transmission frame.

15. The apparatus of claim 11 wherein the one or more sector messages are  
10 separately transmitted in more than one transmission frame.

16. The apparatus of claim 11 wherein said processing means for determining the signal reception quality associated with each of the one or more received sector messages comprises:

15 means for measuring any of bit error rate, signal strength, carrier to interference ratio and delay spread associated with each of the one or more sector messages.

17. The apparatus of claim 11 wherein said transmission means for sending an  
20 antenna selection request message from the mobile terminal to the base station comprises:

transmission means for sending the antenna selection request message over a portion of a random access channel, in a mobile access protocol, specifically reserved for the selected antenna.

25

18. The apparatus of claim 11 wherein the antenna selection request is part of a connection set-up request generated by the mobile terminal.

19. The apparatus of claim 11 wherein the antenna selection request is part of a

-11-



change of antenna request generated by the mobile terminal.

20. The apparatus of claim 19 wherein said transmission means for sending an antenna selection request message from the mobile terminal to the base station

5 comprises:

transmission means for sending the antenna selection request message over a portion of an uplink channel, in accordance with a mobile access protocol, specifically reserved for the antenna through which the mobile terminal is presently operating.

1/2

*FIG. 1**FIG. 2*

2/2




FIG. 3




FIG. 4



# INTERNATIONAL SEARCH REPORT

International Application No

PCT/SE 99/01351

**A. CLASSIFICATION OF SUBJECT MATTER**  
IPC 7 H04Q7/38

According to International Patent Classification (IPC) or to both national classification and IPC

**B. FIELDS SEARCHED**

Minimum documentation searched (classification system followed by classification symbols)

IPC 7 H04Q

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

**C. DOCUMENTS CONSIDERED TO BE RELEVANT**

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	EP 0 660 633 A (NIPPON ELECTRIC CO) 28 June 1995 (1995-06-28)  column 8, line 9 -column 10, line 9 ----	1,2,4,6, 8-12,14, 16,18-20
A	EP 0 847 209 A (NORTHERN TELECOM LTD) 10 June 1998 (1998-06-10)  column 5, line 57 -column 6, line 16 column 9, line 19-45 -----	1,6,8,9, 11,16, 18,19

☐ Further documents are listed in the continuation of box C.



Patent family members are listed in annex.

\* Special categories of cited documents :

- "A" document defining the general state of the art which is not considered to be of particular relevance
- "E" earlier document but published on or after the international filing date
- "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- "O" document referring to an oral disclosure, use, exhibition or other means
- "P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

"&" document member of the same patent family

Date of the actual completion of the international search

14 December 1999

Date of mailing of the international search report

21/12/1999

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2  
NL - 2280 HV Rijswijk  
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,  
Fax: (+31-70) 340-3016

Authorized officer

Weinmiller, J

# INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/SE 99/01351

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
EP 0660633 A	28-06-1995	JP 2586316 B JP 7184254 A US 5606727 A	26-02-1997 21-07-1995 25-02-1997
EP 0847209 A	10-06-1998	US 5903826 A CA 2222001 A	11-05-1999 06-06-1998

